



ZC-RUBBER PRODUCT

# 2016 TYRE CATALOGUE



- Super value tyre applicable for trailer axle
- Improved tread compound and tyre casing provide superb balance between cost and performance



# AT161

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |              |           |            |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|--------------|-----------|------------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | Single (kPa) | Dual (kg) | Dual (kPa) |
| 11R22.5     | H/16    | 148/145M      | 15.5             | 8.25         | 1054                  | 279                | 3150                                          | 850          | 2900      | 850        |
| 12R22.5     | J/18    | 152/149L      | 15.5             | 9.00         | 1085                  | 300                | 3550                                          | 930          | 3250      | 930        |
| 295/80R22.5 | J/18    | 152/149M      | 15.0             | 9.00         | 1050                  | 298                | 3550                                          | 900          | 3250      | 900        |
| 315/80R22.5 | J/18    | 154/151M      | 15.5             | 9.00         | 1082                  | 312                | 3750                                          | 830          | 3450      | 830        |



- Improved close shoulder helps to improve even wear resulting in long tread life
- Straight simple rib pattern improves even wearing and efficient water evacuation for excellent wet traction and handling
- Cross rib sipes slice through water for solid control on wet roads



## AT160

| Size    | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |              |           |            |
|---------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|--------------|-----------|------------|
|         |         |               |                  |              |                       |                    | Single (kg)                                   | Single (kPa) | Dual (kg) | Dual (kPa) |
| 11R22.5 | H/16    | 148/145M      | 14.2             | 8.25         | 1054                  | 279                | 2800                                          | 720          | 2650      | 720        |



- Wide base multi-rib trailer tyres with durable compound to deliver excellent value
- Strong casing structure offers multiple retreads and lower total cost
- Improved tread design promises outstanding stability with optimized footprint and better tyre life



# AT131

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |              |           |            |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|--------------|-----------|------------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | Single (kPa) | Dual (kg) | Dual (kPa) |
| 385/65R22.5 | L/20    | 160K(158L)    | 15.5             | 11.75        | 1072                  | 389                | 4250                                          | 850          | -         | -          |



- Value tyre suitable for drive axle
- Special tread compound and tyre casing offers good tyre mileage for price sensitive customers
- Computer designed tread guarantees good traction for highway service in all season conditions



# AD153

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |       |           |       |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|-------|-----------|-------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | (kPa) | Dual (kg) | (kPa) |
| 295/80R22.5 | J/18    | 152/149M      | 19.0             | 9.00         | 1050                  | 298                | 3550                                          | 900   | 3250      | 900   |



- Value tyre suitable for drive axle
- Aggressive tread blocks with special tread compound provide good traction on paved roads for price-oriented customers
- Special tread design promises remarkable footprint and even wear to extend tread life



# AD156

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |              |           |            |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|--------------|-----------|------------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | Single (kPa) | Dual (kg) | Dual (kPa) |
| 11R22.5     | H/16    | 148/145L      | 20.6             | 8.25         | 1065                  | 279                | 3150                                          | 850          | 2900      | 850        |
| 12R22.5     | J/18    | 152/149L      | 19.0             | 9.00         | 1085                  | 300                | 3550                                          | 930          | 3250      | 930        |
| 295/80R22.5 | J/18    | 152/149M      | 19.0             | 9.00         | 1050                  | 298                | 3550                                          | 900          | 3250      | 900        |



- Designed for both steer and trailer axle
- Four ribs design provides excellent footprint and more contact on the road surface
- Special tyre casing and compound offer great value by longer mileage with less cost



# AZ171

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |              |           |            |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|--------------|-----------|------------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | Single (kPa) | Dual (kg) | Dual (kPa) |
| 295/80R22.5 | J/18    | 152/149M      | 16.0             | 9.00         | 1050                  | 298                | 3550                                          | 900          | 3250      | 900        |
| 315/80R22.5 | J/18    | 154/151M      | 15.5             | 9.00         | 1082                  | 312                | 3750                                          | 830          | 3450      | 830        |



- Wide, deep tread helps provide long tread life in regional conditions
- Zig-zag ribs ensure even wear and grip on wet, dry and snowy roads



# AZ188

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |       |           |       |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|-------|-----------|-------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | (kPa) | Dual (kg) | (kPa) |
| 315/80R22.5 | J/18    | 154/151M      | 15.5             | 9.00         | 1076                  | 312                | 3750                                          | 830   | 3450      | 830   |



- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



# AZ126

| Size        | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |       |           |       |
|-------------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|-------|-----------|-------|
|             |         |               |                  |              |                       |                    | Single (kg)                                   | (kPa) | Dual (kg) | (kPa) |
| 11R22.5     | H/16    | 148/145M      | 16.8             | 8.25         | 1054                  | 279                | 3150                                          | 850   | 2900      | 850   |
| 12R22.5     | J/18    | 152/149L      | 16.0             | 9.00         | 1085                  | 300                | 3550                                          | 930   | 3250      | 930   |
| 295/80R22.5 | J/18    | 152/149L      | 16.0             | 9.00         | 1044                  | 298                | 3550                                          | 900   | 3250      | 900   |
| 315/80R22.5 | J/18    | 154/151M      | 15.5             | 9.00         | 1076                  | 312                | 3750                                          | 830   | 3450      | 830   |



- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



# AZ026

| Size     | LR / PR | Service index | Tread Depth (mm) | Standard Rim | Overall Diameter (mm) | Section Width (mm) | Max. Load Capacity at Cold Inflation Pressure |       |           |       |
|----------|---------|---------------|------------------|--------------|-----------------------|--------------------|-----------------------------------------------|-------|-----------|-------|
|          |         |               |                  |              |                       |                    | Single (kg)                                   | (kPa) | Dual (kg) | (kPa) |
| 10.00R20 | J/18    | 149/146J      | 15.0             | 7.5          | 1054                  | 278                | 3250                                          | 930   | 3000      | 930   |
| 11.00R20 | J/18    | 152/149K      | 16.0             | 8.0          | 1085                  | 293                | 3550                                          | 930   | 3250      | 930   |
| 12.00R20 | J/18    | 154/151K      | 16.5             | 8.5          | 1125                  | 315                | 3750                                          | 830   | 3450      | 830   |
| 12.00R24 | L/20    | 160/157K      | 16.0             | 8.5          | 1226                  | 315                | 4500                                          | 900   | 4125      | 900   |



**ZHONGCE RUBBER GROUP CO., LTD.**